
AT-LAST-A-SEAL® SEALING SYSTEM

- ✓ Simple Installation
- ✓ Low Maintenance
- ✓ Corrosion Resistant
- ✓ Fast Delivery
- ✓ Super Heavy Duty
- ✓ Floating Seal



Steel, self-adjusting retaining chains create a tight seal that free-floats on the belt prolonging belt and seal life.

Seamless 65-75 durometer EPDM rubber is weather, UV, and ozone resistant.





- At-Last-A-Seal® provides a 'live' seal and moves freely on the chute wall requiring minimal, if any, maintenance.
- Self-adjusts to the load weight on the belt increasing the life of the seal.
- No seams or joints means no leakage and no maintenance.
- No clamps or mounting brackets needed for installation.
- Protects the chute wall by acting as a chute liner.
- Available in continuous lengths up to 600'.
- Now available for standard or flat belts.
- · Ideal with Simplicity Slider System.

WHO IS ARCH ENVIRONMENTAL?

Manufacturer and worldwide distributor of preferred bulk conveyor components since 1975.





800.553.4567 www.archenv.com

MECHANICAL DIVISION

Belt Cleaners • Belt Alignment • Sealing Systems Dust Control Systems • Impact/Slider Systems

ELECTRICAL DIVISION

Belt Scales • Metal Detectors • Pull Cord Switches Belt Protection Devices • Conveyor Control Systems



AT-LAST-A-SEAL® SEALING SYSTEM

TEMP. RANGE: -40C to +107C (225F) CONTINUOUS +121C(+250F) SHORT TERM

MATERIAL: BLACK EPDM RUBBER

EXCELLENT RESISTANCE TO OZONE, UV, AND WEATHER

HARDNESS: 65-75 SHORE A

AVERAGE COEFFICIENT OF FRICTION

FOR 'ATLASTASEAL' TO CONVEYOR BELT: .38

(16 BELT SAMPLES USED)

APPROXIMATE WEIGHT: 5 pounds per foot
MAXIMUM STRUCTURE THICKNESS = 1/2"
SUPPLIED IN CONTINUOUS LENGTHS UP TO 600 FEET

